

Sounds Heavenly

Attenuated Converter for Beolab* Speakers

Thank you for purchasing a Sounds Heavenly Attenuated Converter for your Bang and Olufsen speakers. This high-quality device contains precision electronics to allow you to connect a pair of Bang and Olufsen Beolab active loudspeakers to the speaker terminals of your classic Bang and Olufsen or non-B&O power amplifier/receiver. This converter is suitable for home or professional use and is designed to be left permanently connected to the amplifier and speakers in dry, indoor conditions only.

Fitting Instructions:-

1. Locate the output sockets on the converter. These are RCA (also called Phono or Cinch) sockets. Connect these outputs to the sockets on your Beolab speakers marked "Line" using a pair of our Line Input Cables for Beolab Speakers (not included with the converter) and set the input switches on both speakers to "Line" (connect the plug with red markings to the right-hand speaker and the plug with black markings to the left-hand speaker).
2. Identify the speaker connections on your amplifier and ensure that you have ordered the correct input connections on the converter to fit these. If you have requested bare wire ends or individual terminals on the cable, please ensure that you identify the left and right sides of the cable (the right-hand cable has a red band fitted) and connect the brown wire to the left negative speaker terminal. Connect the black wire to the right negative terminal. Connect the green wire to the left positive terminal and the grey wire to the right positive terminal. If you have 2 pin DIN plugs fitted, simply identify the left and right plugs using the wire colours above and connect these to the correct sockets on the amplifier.
3. Using a small screwdriver, turn both Level controls to Minimum (anti-clockwise), then give them approx. ¼ turn clockwise.
4. Turn on the power to your audio system and speakers.
5. The Level controls can now be adjusted as required (in very small amounts) to give a comfortable listening volume. Please note that some amplifiers produce a small amount of background noise when used with this converter and that this may prevent the speakers from switching to standby automatically. Reducing the Level controls (by turning them anti-clockwise) can help to prevent this situation.
6. Sit back and enjoy the music!

Important note: Never connect your Beolab speakers directly to a power amplifier using standard cables, as this can result in serious and expensive damage to the equipment (and probably your ears!)